IPC-817

INDUSTRIAL PANEL COMPUTER STAINLESS SERIES



Industrial Computer Solutions





Artech Stainless Series 17" Touchscreen Industrial Panel PC facilitates the digital transformation process in manufacturing environments with its wide screen and capacitive touch technology. Equipped with a Celeron J6412 processor, this device offers superior performance and various power supply options.

MAIN ADVANTAGES

- Durability and Performance: Ensure continuous operation of your facility with Artech Industrial Panel Computers that operate smoothly even in harsh industrial conditions.
- Cost and Energy Savings: Reduce your total cost of ownership through energy efficiency and low-cost operation.

KEY FEATURES

- Celeron J6412 Processor: Provides high processing performance.
- Resistive Touch Technology: Delivers a seamless touch experience.
- 12V and 24VDC Power Supply Options: Offers flexible power solutions.
- Easily Removable and Replaceable Disk Slot: Simplifies data management.
- 0-60 °C Operating Performance: Stable operation across a wide temperature range.
- IP65 Front Panel Protection: Superior protection against dust and water.
- Stainless Steel Case: Ensures durability and long life.
- 24/7 Operation Suitable: Perfect for uninterrupted operations.

TECHNICAL SPECIFICATIONS

| ORDER CODE | |
|-----------------------|-------------------------------------|
| CPU | : Celeron J6412 |
| PSU | : 12 /24 |
| RAM | : R4 / R8 / R16 / R32 / R64 |
| HDD | : 64 / 128 / 256 / 512 / 1TB |
| Wi-Fi | : Optional |
| SYSTEM | |
| CPU | : Celeron J6412 |
| Memory | : DDR4-3200, 2*SO-DIMM, up to 64 GB |
| Video RAM | : Intel® HD Graphics |
| Chipset | : Intel |
| Watchdog Timer | : 255 Level Reset |
| System Fan | : Fanless |
| INPUT/OUTPUT | |
| Serial Port | : 3 x (RS232/RS422/RS485) |
| Paralel Port | : N.A. |
| USB Port | : 4 (2 x USB 3.0 , 2 x USB 2.0) |
| LAN | : 2 x Ethernet 10/100/1000 BaseT |
| Wireless LAN | : 802.11 b / g / n (Optional) |
| Audio | : Realtek® 5.1 channel HDA Codec, |
| | with MIC/Line-out and Amplifier |
| Expansion Slot | : Mini PCIe |
| DATA STORAGE | |
| HDD Type | : Fixed / Slide - Easy Change |
| SSD | : M.2 / 2.5" SSD 64 GB / 128 GB / |
| | , , |

256 GB / 512GB / 1TB

| FEED | |
|------------------|-----------------------------------|
| Input | : 12 or 24 VDC |
| LCD SCREEN | |
| Type / Size | : 17" (4:3) |
| Max. Resolution | : 1280x1024 |
| Pixel Pitch | : 0.297(H) x 0.297(W) |
| Max. Color | : 16.7 M |
| Brightness | : 350cd |
| Contrast Ratio | : 1000/1 |
| Viewing Angle | : 160°(H),160°(V) |
| Back Light MTBF | : 50,000 Hours |
| Touch Screen | : Capasitive (Flat Touch) |
| EXTRA VIDEO OUTP | UT |
| Туре | : 2 x HDMI Display Output |
| MECHANICAL & ENV | /IRONMENTAL FEATURES |
| Working Temp. | : 0~60℃ |
| Storage Humidity | : 5~95% (Non-Condensing) |
| Case | : Dust Proof Stainless Steel Body |
| Front Frame | : IP65 Aluminum |
| Mounting | : Pano, Kiosk or Vesa |

